

# Specyfikacja 5200

## Aluminiowe rusztowanie jezdne 5200



Wysokość najwyższego pomostu (m)	2.20	4.20 <sup>1</sup>	6.20	8.20 <sup>1</sup>	10.20	12.20
Wysokość robocza (m)	4.20	6.20	8.20	10.20	12.20	14.20

1.35 x 1.85 m	<b>Numer katalogowy</b>	pomosty standardowe		C520001	C520003	C520005	C520007	C520009	C52001
		pomosty Fiber-Deck®		C520002	C520004	C520006	C520008	C520010	C52001:
	<b>Wykaz elementów</b>	<b>Art.nr</b>	<b>Waga (kg)</b>						
	Rama 1,35 x 2,0 m	301607	10,9	2	4	6	8	10	12
	Rama poręczowa 1,35 x 1,0 m	302920	4,1	2	2	2	2	2	2
	Koło jezdne Ø 200 mm	511230	5,2	4	4	4	4	4	4
	Pomost 1,85 m z klapą	304410	14,8	1	1	2	2	3	3
	Pomost 1,85 m bez kłapy	304420	14,4	1	1	2	2	3	3
	<b>Pomost Fiber-Deck® 1,85 m z klapą</b>	<b>305210</b>	<b>10,8</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
	<b>Pomost Fiber-Deck® 1,85 m bez kłapy</b>	<b>305220</b>	<b>10,1</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
Stężenie ukośne 1,85 m	303721	2,0	4	8	12	16	20	24	
Stężenie poziome 1,85 m	303704	1,9	6	6	10	10	14	14	
Stabilizator teleskopowy Easy-Lock®	305613	7,6	-	4	4	4	4	4	
Aluminiowa burtą poprzeczna 2x 1,35 m	305506	6,6	1	1	1	1	1	1	
Aluminiowa burtą podłużna 2x 1,85 m	305501	8,8	1	1	1	1	1	1	

1.35 x 2.45 m	<b>Numer katalogowy</b>	pomosty standardowe		C520013	C520015	C520017	C520019	C520021	C52002:
		pomosty Fiber-Deck®		C520014	C520016	C520018	C520020	C520022	C52002:
	<b>Wykaz elementów</b>	<b>Art.nr</b>	<b>Waga (kg)</b>						
	Rama 1,35 x 2,0 m	301607	10,9	2	4	6	8	10	12
	Rama poręczowa 1,35 x 1,0 m	302920	4,1	2	2	2	2	2	2
	Koło jezdne Ø 200 mm	511230	5,2	4	4	4	4	4	4
	Pomost 2,45 m z klapą	304510	18,7	1	1	2	2	3	3
	Pomost 2,45 m bez kłapy	304520	18,4	1	1	2	2	3	3
	<b>Pomost Fiber-Deck® 2,45 m z klapą</b>	<b>305310</b>	<b>13,7</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
	<b>Pomost Fiber-Deck® 2,45 m bez kłapy</b>	<b>305320</b>	<b>13,3</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
Stężenie ukośne 2,45 m	303716	2,5	4	8	12	16	20	24	
Stężenie poziome 2,45 m	303706	2,3	6	6	10	10	14	14	
Stabilizator teleskopowy Easy-Lock®	305613	7,6	-	4	4	4	4	4	
Aluminiowa burtą poprzeczna 2x 1,35 m	305506	6,6	1	1	1	1	1	1	
Aluminiowa burtą podłużna 2x 2,45 m	305502	10,9	1	1	1	1	1	1	

1.35 x 3.05 m	<b>Numer katalogowy</b>	pomosty standardowe		C520025	C520027	C520029	C520031	C520033	C52003:
		pomosty Fiber-Deck®		C520026	C520028	C520030	C520032	C520034	C52003:
	<b>Wykaz elementów</b>	<b>Art.nr</b>	<b>Waga (kg)</b>						
	Rama 1,35 x 2,0 m	301607	10,9	2	4	6	8	10	12
	Rama poręczowa 1,35 x 1,0 m	302920	4,1	2	2	2	2	2	2
	Koło jezdne Ø 200 mm	511230	5,2	4	4	4	4	4	4
	Pomost 3,05 m z klapą	304510	23,6	1	1	2	2	3	3
	Pomost 3,05 m bez kłapy	304520	23,3	1	1	2	2	3	3
	<b>Pomost Fiber-Deck® 3,05 m z klapą</b>	<b>305310</b>	<b>17,3</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
	<b>Pomost Fiber-Deck® 3,05 m bez kłapy</b>	<b>305320</b>	<b>16,7</b>	<b>1</b>	<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>3</b>
Stężenie ukośne 3,05 m	303716	2,7	4	8	12	16	20	24	
Stężenie poziome 3,05 m	303706	2,6	6	6	10	10	14	14	
Stabilizator teleskopowy Easy-Lock®	305613	7,6	-	4	4	4	4	4	
Aluminiowa burtą poprzeczna 2x 1,35 m	305506	6,6	1	1	1	1	1	1	
Aluminiowa burtą podłużna 2x 3,05 m	305503	12,8	1	1	1	1	1	1	